



# IDC AXS+

## Readers



Reference image only\*

*IDCUBE's AXS+ is the only reader in the world in its category to support all forms of virtual and digital credentials: smartcards, classic & dynamic QR codes, mobile credentials, and PINs.* The reader design incorporates the dynamic requirements of short-term & long-term users as well as ease of credential issuance & distribution.

The reader is best suited for smart-spaces for their ever-increasing demand for virtual credentials. Some use-case scenarios are Stadiums, Coworking Spaces, Business Parks, Gated Communities, Corporate Offices, etc.

With their aesthetic, sleek, and convenient form, the AXS+ readers fill all the checkboxes needed for an ideal contemporary smart-space experience. The AXS+ readers are readily compatible with any PACS controller supporting OSDP & Wiegand as the communication interface. Both the variants (Mullion and Gang box) offer unparalleled flexibility and scale to the dynamic nature of future-ready organizations.

### KEY FEATURES

Support all forms of virtual and digital credentials: smartcards, classic & dynamic QR codes, mobile credentials, and PINs

Support for secure clone proof *dynamic QR codes* facilitates online provisioning of credentials and universal compatibility with smart phones

Secured communication with support for OSDP and OSDP SC

Highly adaptive with Bluetooth and NFC-ready features







Easily configurable and upgradable via mobile app and OSDP

Available in 6 different models

Best suited for physical access control in stadiums, coworking spaces, business parks, gated communities and corporate offices

Sleek, and ergonomic design

## AXS+ READER SPECIFICATIONS

	Mullion Mount			Gang box Mount		
	Smart Card Reader	Smart Card + QR Code Reader	Smart Card Reader	Smart Card + QR Code Reader	Smart Card +PIN	Smart Card + QR Code Reader + PIN
Reader Images						
Dimensions (W x D x H)	48mm x 120mm x15mm			80mm x 120mm x15mm		
13.56 MHz / NFC Credential Compatibility	Default: MIFARE Mini, MIFARE 1K, MIFARE 4K, MIFARE Ultralight, MIFARE DESFire EV1, NFC					
Typical Read Range	MIFARE Classic, MIFARE DESFire EV1/EV2 & ISO14443A Single Technology Cards – 1.6 to 4 in (4 to 10 cm)					
Color	Black					
PIN Pad	–				Yes	Yes
QR Code Reader	–	Yes	–	Yes	–	Yes
Operating Voltage	12V DC					
Device Input and Output	Input: RLED,GLED, BZR (Active Low), Output: Tamper					
Communications & Panel Connection	Wiegand and RS-485 Half Duplex (OSDP) via Pigtail (18 in / 0.5 m) or Terminal Strip					
Device Management	IDCUBE Reader Manager Mobile App					
Certifications	IP65, FCC, CE, RoHS Compliant					
Housing Materials	Polycarbonate					
Warranty	5 years					
Variant Model Numbers	AXS+ MNND	AXS+ MQND	AXS+ GNND	AXS+ GQND	AXS+ GNKD	AXS+ GQKD

### USA

IDCUBE Corporation,  
20, Corporate Place South, 2nd Floor,  
Piscataway,  
New Jersey – 08854, USA

### UAE

IDCUBE - FZE  
Techno Hub 1 – Office G 042,  
Dubai Silicon Oasis,  
Dubai, UAE

### INDIA

IDCUBE Identification Systems Pvt. Ltd.  
B-19, Sector-2, NOIDA 201301,  
UP, INDIA

[contact@idcubesystems.com](mailto:contact@idcubesystems.com) | [www.idcubesystems.com](http://www.idcubesystems.com)

