

# MIFARE® DESFire® EV1 Credentials

MIFARE DESFire EV1 Card • 1450, 1456

MIFARE DESFire EV1 / HID Prox Combo Card • 1451, 1457

- ▶ **High Security** - Mutual authentication, AES 128, DES and triple-DES data encryption and unique 56-bit serial number.
- ▶ **Read/Write Functionality** - Perfect for multi-functional memory applications.
- ▶ **Transition Solution** - Add smart card applications to existing HID proximity technology access control systems.
- ▶ **True Credit Card Thickness** - Use with all direct image and thermal transfer printers.



## ACCESS interoperability.

HID MIFARE® DESFire® EV1 cards are designed for diverse applications that demand the highest levels of security, including access control and biometric identification, cashless vending, public transportation, ticketing and customer loyalty cards. Available in PVC and Composite PET/PVC card construction, the HID MIFARE DESFire EV1 card is exceptionally durable and can accept an embeddable contact chip for logical access and biometric ID systems.

HID MIFARE DESFire EV1 credentials have 8 Kbytes of dynamic memory arranged in easy-to-define application folders and data files. MIFARE DESFire EV1 data can be encrypted with the highly secure Advanced Encryption Standard (AES 128) algorithm assuring that data in the card is secure before, during and after the transaction, as well as between folders and files within the credential itself.

13.56 MHz MIFARE DESFire EV1 read/write technology combined with 125 kHz HID Prox technology can be integrated into a single ISO standard thickness card (custom programming with Indala formats is also available). This converged card is suitable for adding MIFARE DESFire EV1 applications to an existing HID Prox-based access control system.

When security and performance count most, HID's MIFARE DESFire EV1 cards can be produced with visual security and anti-counterfeiting features such as holograms, ultra-violet fluorescent inks, micro-printing or a custom logo to quickly and easily identify genuine cards.

### Key Features of MIFARE DESFire EV1 Technology

- ▶ **Proven, Reliable Technology** - MIFARE DESFire EV1 is based on open global standards for security, and is interoperable with existing MIFARE infrastructures.\*
- ▶ **Fast Processing and Data Communication** - Transaction times are less than 100 milliseconds for a typical secure ticketing transaction.
- ▶ **Standards Compliant** - MIFARE DESFire EV1 is fully compliant with ISO 14443A 1-4, and has been awarded CC EAL 4+ for card security.

\*MIFARE DESFire EV1 is not compatible with the PIV read application used with a DESFire 0.6 card

# Features

## Long Life

Passive, no-battery design allows for an infinite number of reads.

## Durability

Strong, flexible and resistant to damage.

## Photo ID Compatible

Print directly to the card with a direct image or thermal transfer printer.

## PVC Card Surface

Card is optimized for dye sublimation printing.

## Customizable

Specify your own text or graphics artwork.

## Thin

0.030" (0.076 cm) card can be carried with credit cards in a wallet or purse. Use with a badge holder and strap clip or lanyards for an attractive photo ID badge.

## Many Ordering Options

Including magnetic stripe, external card numbering, custom artwork and contact smart chip module.

### MIFARE® DESFire® EV1

### MIFARE® DESFire® EV1 with HID PROX

<b>Base Part Number</b>	PVC - 1450 PET/PVC - 1456	PVC - 1451 PET/PVC - 1457
<b>Operating Frequency</b>	13.56 MHz	13.56 MHz (MIFARE DESFire EV1) 125 kHz (HID PROX)
<b>RF Interface</b>	ISO 14443 A, Parts 1-4 (DESFire EV1)	
<b>Typical Maximum Read Range</b>	DESFire: Up to 4" (10 cm)	DESFire: Up to 4" (10 cm) Prox: 2" - 4.5" (5.0 - 11.4 cm)
<b>Transaction Time</b>	< 100 ms	
<b>Baud Rate</b>	Activation at 106 kbps; Data transfer up to 848 kbps	
<b>Memory Type</b>	EEPROM 8 Kbytes	
<b>Memory Structure</b>	Up to 28 applications, with up to 32 files per application	
<b>Operating Temperature</b>	Model 1450/1451 PVC Cards: -40 to 122°F (-40 to 50°C) Model 1456/1457 Composite Cards: -40 to 158°F (-40 to 70°C)	
<b>Operating Humidity</b>	5% - 95% Non-Condensing	
<b>Write Endurance</b>	100,000 cycles min.	
<b>Data Retention</b>	10 years min	
<b>Materials and Finish</b>	Gloss white/white PVC or PVC/Polyester Composite	
<b>Weight</b>	0.20 oz (6.0 g)	0.24 oz (6.8 g)
<b>Programming</b>	Factory or Field	
<b>Card Marking</b>	Inkjet standard, Laser Engraving optional	
<b>Custom Graphics</b>	Optional	
<b>Magnetic Stripe</b>	Optional	
<b>Printable</b>	Yes (white/white card)	
<b>Slot Punch</b>	Not Available (MIFARE DESFire EV1 cards do not allow a slot punch)	
<b>Visual Security Options</b>	Optional	
<b>Additional Security Options</b>	Corporate 1000	
<b>Warranty</b>	Lifetime - see Sales Policy for complete details	

© 2010 HID Global Corporation. All rights reserved. HID and the HID logo are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

mkt\_04nov2010\_mifaredesfire\_ev1\_ds\_en



#### HID Global Offices:

**Corporate North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Phone: (800) 237-7769  
Phone: +1 (949) 732-2000  
Fax: +1 (949) 732-2120

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Tel: +852 3160 9800  
Fax: +852 3160 4809

**Latin America**  
Vasco de Quiroga No. 1900 - 202  
Centro Ciudad Santa Fe  
Delegacion Alvaro Obregón  
01210 México, D.F.  
Phone: +52 55 5081 1650  
Fax: +52 (55) 5081-1670

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Tel: +44 1440 714 850  
Fax: +44 1440 714 840